

SERVER HARDWARE FOR CONTENT MANAGEMENT SERVER



Part Code	STM-P
Chassis	19" 4U Rack Mountable
Operating System #	W10P / W11P / W10IOT
Processor options#	i7 / i9 / Xeon* Processor
RAM#	16GB DDR or Higher
Storage#	2x 500GB with Raid 1
Networking	Dual Gigabit Ethernet Controller inbuilt
Cooling	Forced cooling, Active Heatsink
Indicators	LED's for HDD activity and Power status
Output support	HDMI / VGA
Switches	Power On/Off and System Reset
Outputs#	HDMI/VGA Output: 1920x1080
Format Support	JPEG, PNG, MJPEG, MPEG-2 , MPEG-4, H.264, etc..
Audio	Aux Out 3.5mm , High Definition Audio CODEC
Redundancy support	Includes 500W Single PWS or Redundant Power Supply (Optional on chargeable basis)
Power Supply	AC Voltage 100 - 240V, 50 - 60Hz
Temperature	Operating Temperature: 0° to 35°C (32° to 95°F)
	Non-operating Temperature: - 40° to 70°C (-40° to 158°F)
Humidity	Humidity: 10 – 90% non- condensing
Sound Level	~ 50db
Application	Streme Content Manager Application
Dimensions	Less than 650mm Depth, 19" Wide, 4U High
** Special features available on request. Please refer to part number list.	
## Depends on the license and sales offer and may differ for case to case basis	
All Specifications subject to change without prior notice in line with incorporating latest technical advances in products.	